

Dimensionair® Air Gages

Hoses

Supply hoses and hoses between Dimensionair and air tooling.

Order No.	Description	Thread
AHO-2	1.5m/5ft Air Supply Hose. Fits all Dimensionair models. (rubber)	7/16-20
AHO-1	0.9m/3ft Air hose for tooling for Models 1250:1 – 8000:1. (Tygon)	3/8-32
AHO-8	1.5m/5ft Air hose for tooling on Models 2500:1 – 8000:1. (Tygon)	3/8-32
AHO-10	1.8m/6ft Air hose for Models 1250:1 – 8000:1. (Tygon)	3/8-32
AHO-20	0.9m/3ft Air hose for tooling on Models 10000:1 – 32000:1. (Tygon)	9/32-40
ARG-1	Replacement O-ring for AHO-1, -8, -10 Hoses and AHA-4, -5, -6, -20 Handles.	
ARG-6	Replacement O-ring for AHO-20 Hose, AHA-23 and -24 Handles.	
ARG-10	For AEX-1, AEX-2 and AHA-28	

Traps and Filters

Good gaging practice requires clean, dry air for gage performance. Dimensionair Models are furnished with a particle filter. Shop air contains water and oil, which should be removed, using Model **AFL-24** Oil and Water Separator Trap.

Model No.	Description
AFL-10	Particle Filter (normally furnished on all Dimensionair Models). Filter size: 5 microns; Maximum pressure: 250 p.s.i.; maximum working temperature: 175°F.
AFL-24	Oil and Water Separator Trap, includes mounting hardware. Filtering capacity: 99.7% removal of oil and water; filter size: 3-6 microns; maximum pressure: 150 p.s.i.; flow rate: 20 cubic feet of air/minute @ 80 p.s.i.
AFL-23	Replacement cartridge for AFL-24.
AFL-21	Replacement cartridge for AFL-10.
AAD-263	Retrofit Kit for AFL-9




AFL-24 Trap


Mounting Brackets for AirProbes® and Jetprobes

Adjustable Mounting Bracket
Order No. AT-29

Allows for $\pm 7/16$ in adjustment of probe using a hex wrench.




Square Bracket
Order No. AAD-67
1/4-20 mounting thread.



"L" Bracket
Order No. AAD-66

For mounting AirProbes and other .375in dia. Gage Heads on Comparator Stands.



"T" Bracket
Order No. AAD-91
Flange mounted, two 4.3mm/.169in through holes.

