

CERAMIC DUPLEXER

PART NO. : WVX-800P860-48A810

◆ APPLICATION

> LTE(700) Band System

◆ FEATURE

> High Reliability
> **RoHS Compliant**

◆ ELECTRICAL SPECIFICATION



ITEM	SPECIFICATION	
	Low	High
Center Frequency	800 MHz	860 MHz
Operating Bandwidth	48 MHz	18 MHz
Insertion Loss @Center Frequency	2.0dB Max	2.0dB Max
Ripple in BW	0.7dB Max	0.5dB Max
Return Loss in BW	15dB Min.	15dB Min.
Rejection(Min.)	40dB@851~869MHz	40dB@776~824MHz
Input Power	5 Watt Max.	
In/Out Impedance	50 Ohms	

◆ ENVIRONMENTAL SPECIFICATIONS

ITEM	SPECIFICATION
Operating Temperature Range	-40°C to +85°C
Dimension	43.0 x 18.0 x 9.2max. (mm)
Filter Type / Resonator Poles	Monoblock PCB type / 8mm 10Pole

CERAMIC DUPLEXER

◆ OUTLINE DRWAING



■ :I/O PORT
■ :GROUND

TOLERANCE UNLESS
OTHERWISE SPECIFIED : ± 0.2
DIMENSIONS : mm